



STANDART TİP GMK Y/D SERİSİ KONDENSERLER / Standart Type GMK Y/D Series Condensers

GMK Y/D - Ø500mm (1210dd / 900dd)	KAPASİTE Capacity		HAVA DEBİSİ Air Cap.		ISITMA YÜZEYİ Heat Transfer Surface	BORU HACMI Tube Volume	FAN SAYISI Quantity of Fan	FAN MOTORU Fan Motor				SES SEVİYESİ Sound Level		BOYUTLAR / Dimensions						BAĞLANTILAR Connections	
	1/230V 50 Hz	1/230V 50 Hz	1/230V 50 Hz	1/230V 50 Hz				GÜÇ / AKIM Power/Current		1/230V 50 Hz	1/230V 50 Hz	1/230V 50 Hz	1/230V 50 Hz	A	B	D	H	G	E	Giriş (Ø) Inlet	Çıkış (Ø) Outlet
	-	-	-	-				kw	A	kw	A	dB(A)		mm	mm	mm	mm	mm	mm	mm	mm
GMK Y/D 50.1.1-1325	23,0	18,1	7050	5050	49,2	9,6	1x1	0,77	3,4	0,29	1,25	47	41	880	1050	900	985	500	970	28	22
GMK Y/D 50.1.1-1321	24,1	18,8	6800	4900	57,9			0,77	3,4	0,29	1,25	47	41	880	1050	900	985	500	970	28	22
GMK Y/D 50.2.1-1325	46,0	36,3	14100	10100	98,3	19,2	1x2	1,54	6,8	0,58	2,5	50	44	1680	1850	900	985	500	970	35	28
GMK Y/D 50.2.1-1321	48,2	37,7	13600	9800	115,8			1,54	6,8	0,58	2,5	50	44	1680	1850	900	985	500	970	35	28
GMK Y/D 50.3.1-1325	69,8	55,0	21150	15150	147,5	28,7	1x3	2,31	10,2	0,87	3,75	52	46	2480	2650	900	985	500	970	35	28
GMK Y/D 50.3.1-1321	73,0	57,0	20400	14700	173,7			2,31	10,2	0,87	3,75	52	46	2480	2650	900	985	500	970	35	28
GMK Y/D 50.4.1-1325	92,2	72,6	28200	20200	196,6	38,3	1x4	3,08	13,6	1,16	5	53	47	3280	3450	900	985	500	970	35	28
GMK Y/D 50.4.1-1321	96,5	75,5	27200	19600	231,6			3,08	13,6	1,16	5	53	47	3280	3450	900	985	500	970	35	28
GMK Y/D 50.4.2-1325	92,2	72,6	28200	20200	196,6	38,3	2x2	3,08	13,6	1,16	5	53	47	1680	1850	1600	985	500	970	35	28
GMK Y/D 50.4.2-1321	96,5	75,5	27200	19600	231,6			3,08	13,6	1,16	5	53	47	1680	1850	1600	985	500	970	35	28
GMK Y/D 50.6.2-1325	140,0	110,0	42300	30300	294,9	57,5	2x3	4,62	20,4	1,74	7,5	55	49	2480	2650	1600	985	500	970	42	35
GMK Y/D 50.6.2-1321	146,0	114,0	40800	29400	347,4			4,62	20,4	1,74	7,5	55	49	2480	2650	1600	985	500	970	42	35
GMK Y/D 50.8.2-1325	184,4	145,2	56400	40400	393,2	76,6	2x4	6,16	27,2	2,32	10	56	50	3280	3450	1600	985	500	970	54	42
GMK Y/D 50.8.2-1321	193,0	151,0	54400	39200	463,2			6,16	27,2	2,32	10	56	50	3280	3450	1600	985	500	970	54	42